

Features

- **Premium quality LiFePO₄ technology**
 - Built with A-grade cells & integrated smart battery management system.
- **Stackable modular design**
 - Designed for seamless expansion of capacity in increments of 14.5kWh.
- **Operational lifespan of 10 years**
 - Guaranteed to retain >80% of original capacity at end-of-life (at 1 cycle/day).
- **Serial / CAN compatible** with leading inverters & other relevant peripherals.
- **10 year product warranty.**



Technical Specifications

GENERAL SPECIFICATIONS

Battery chemistry	Lithium Iron Phosphate (LiFePO ₄)
Nominal voltage	26VDC
Usable capacity	14 560Wh @C2, 25°C
Operating voltage range	24V ~ 27.6V
Operating temperature range	Charge: 0°C ~ 50°C Discharge: -10°C ~ 50°C
Cycle life @100% DoD, C2, 25°C	>3600 cycles (<20% fade) 7000 cycles (<40% fade)
Cycle life @ 80% DoD, C2, 25°C	>5000 cycles (<20% fade) 9000 cycles (<40% fade)
Cycle life @70% DoD, C2, 25°C	>7000 cycles (<20% fade) 12000 cycles (<40% fade)
Dimensions	370 x 262 x 870mm (W x H x D) incl. mounting extrusions.
Net weight (unboxed)	±104kg

VOLTAGE & CURRENT

Bulk voltage (operational max.)	27.6V
Low voltage (min).	24V
Charge current (max.)	240A continuous
Discharge current (max.)	320A continuous 400A burst (for < 1 minute) 1200A peak (for < 2 seconds)
Charge power (max.)	Maximum: 7 280W (C2) Recommended: 3 640W (C4)
Discharge power	Maximum: 7 280W (C2) Recommended: 1 456W (C10)
Self-discharge rate	< 2% per month
Charge/discharge efficiency	96% @C2 98% @C10

SAFETY FEATURES

Isolator	400A
Inline fuse	500A
Current over-charge protection	280A
Voltage over-charge protection	< 27.6V (auto cut-off at first V _{cell} ≥ 3.45V)
Voltage over-discharge protection	> 22.8V (auto cut-off at first V _{cell} ≤ 2.85V)